

GV-IO Box 4 Ports



The GV-IO Box 4 provides 4 inputs and 4 relay outputs. It supports both DC and AC output voltages, and provides a USB port for PC connection.

Specifications

Compatible S/W		GV-System version 8.2 or above			
Input	Input	4			
	Input Signal	Dry Contact Wet Contact, 9-30V AC/DC			
Communication	Relay Output	4			
	Relay Status	Normal open			
	Relay Capacitance	<table border="0"> <tr> <td>USB Connection</td> <td>30 VDC, 3A</td> </tr> <tr> <td>RS-232 Connection</td> <td>125 / 250 VAC, 3A 30 VDC, 3A</td> </tr> </table>	USB Connection	30 VDC, 3A	RS-232 Connection
USB Connection	30 VDC, 3A				
RS-232 Connection	125 / 250 VAC, 3A 30 VDC, 3A				
DC IN		DC 12V, 1A			
Address		0-9, A-F			
Terminal Resistance		120 ohm			
Environmental Conditions		0 ~ 50 °C / 32 ~ 122 °F 5% ~ 95% (non-condensing)			
Dimensions (W x H x D)		111.4 x 27.5 x 101 (mm) / 4.39 x 1.08 x 3.98 (in)			
Installation Guide		GV-IO Box 4			

Note: The product does not support 64-bit Windows versions currently.